



# Best Cutting Performance in Elite Class

Powered by a digitally controlled servo system, the Puma IV produces eye-catching graphics with up to 40 ips (1020mm/sec) cutting speed, 500g of cutting force and five meters (16.4 feet) of tracking ability.



P4-132 / P4-132LX



P4-60 / P4-60LX

# Puma IV

- ★ Upgrade to 500 grams of cutting force
- ★ Upgrade to 40 inches per second of cutting speed
- ★ Guaranteed 5 meters tracking
- ★ Section Cutting
- ★ Segmental Positioning (LX models)
- ★ Auto Rotation (LX models)



▶ Vinyl Sign/Custom Decal



▶ Rhinestones



▶ Window Tint Film



### Enhanced AAS II Contour Cutting System (LX Models)

Puma IV LX series features an enhanced Automatic-Aligning System (AAS II) to guarantee precise contour cutting by automatically detecting the registration marks on digitally produced images.



### Section Cutting

Section cutting divides the long plot data into sectional output jobs to gain higher cutting quality and increase precision.



### Segmental Positioning (LX Models)

Puma IV series features Segmental Positioning function which can correct the crooked print.



### Auto Rotation (LX Models)

Puma IV series detects the unique registration marks to distinguish material feeding direction and rotate cutting content automatically.



### Ethernet Connection

Network connection enables multiple Puma IV to be operated by one PC and multiple PCs to share a single unit.

Model Number	P4-60	P4-132	
	P4-60LX	P4-132LX	
Operational Method	Roller -TypeRoller -Type		
Max. Cutting Width	600 mm (23.6 in)	1300 mm (51.18 in.)	
Max. Cutting Length	50m (164 ft)		
Max. Media Loading Width	719 mm (28.3 in.)	1470 mm (57.87 in.)	
Min. Media Loading Width	50 mm (1.97 in)		
Number of Pinch Rollers	2	4	
Acceptable Material Thickness	0.8 mm (0.03 in.)		
Motor Drive	DC Servo Control		
Cutting Force	0~500 g		
Max. Cutting Speed	1020 mm/sec (40 ips) (at 45° direction)		
Acceleration	2.8 G		
Offset	0 ~ 1.0 mm (with an increase of 0.025 mm)		
Memory Buffer	32 MB		
Interfaces	USB 2.0 (Full Speed), Serial (RS-232C) and Ethernet		
Type of Command	HP-GL, HP-GL/2		
Mechanical Resolution	0.006 mm		
Software Resolution	0.025 mm		
Repeatability	±0.1 mm		
Distance Accuracy	±0.254 mm or ±0.1% of move, whichever is greater		
Automatic-Aligning System (AAS II)	Available on Puma IV LX models, including Segmental Positioning and Auto Rotation functions		
Curve & Arc Smoothing	Yes		
Configurable Origin	Yes		
Test Cut Capability	Yes		
Tangential- emulation	Yes		
Repeat	Yes		
Copy	Yes		
Control Panel	LCD (20 digits x 2 lines), 14 Keys, 1 Power LED		
Diameter of Blade	2.5 mm		
Power Supply	AC 100-240V, 50~60 Hz (auto switching)		
Dimension	(HxWxD) mm	220 * 879 * 258 mm	1065 * 1632 * 620 mm (stand including )
	(HxWxD) in	8.76 * 34.61 * 10.16 in.	41.93 * 64.25 * 24.41 in (stand including )
Stand	Optional	Standard	
Media Basket	Optional		

- Compatible with Windows 7 and above & MAC OS X 10.6 and above. (\*Purchasing serial number for "Sure Cuts A Lot" software to work with Mac OS.)
- The specification and data sheet may vary with different materials used. In order to obtain the best output quality, please maintain the machine regularly and properly.
- GCC reserves the right to change the specifications at any time without notice.
- GCC certified material in tracking is Avery MPI 3000.
- The above listed specification values are effective only when operated with media certified by GCC.


[www.GCCworld.com](http://www.GCCworld.com)


GCC Headquarters 4F-1., No.236, Fude 2nd Rd., Xizhi Dist., New Taipei City 22151, Taiwan 886-2-6616-6692 Fax : 886-2-2694-6875  
GCC China No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China 86-512-5726-1515 Fax : 86-512-5726-1518  
GCC Europe B.V. Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands 31-10-458-9367 Fax : 31-10-451-9874  
GCC America, Inc 323 Paseo Tesoro, Walnut, CA 91789, USA 1-909-718-0248 Fax : 1-909-718-0251  
US & Canada Only Toll Free: 1-888-284-5211