C800 Series Specifications



Smallest A3 colour printer, where space is a premium, offering outstanding print quality

If you're looking for a printer that does everything – and does it well, the C800 Series is an ideal choice, especially when space is an issue. Forget old-style huge A3 printers, these will fit into any small office or retail environment, enabling you to print marketing materials in-house, on demand.

The C800 Series will also support all of your everyday printing needs, offering fast and reliable office printing, with document confidentiality.

Key features

- Smallest footprint A3 printer on the market, perfect for retail
- Excellent media flexibility A6 to A3 and up to 1321mm banners
- Up to 35ppm colour print speed
- Fast duplex printing (optional on n variants)
- Paper capacity up to 2,005 sheets and media weights between 64 and 256gsm
- Excellent 1200 x 1200dpi print quality (C843dn)
- Citrix XenApp 7.6 compatibility ideal for virtual network environment



Advanced connectivity

- Wireless Direct offers safe simultaneous connection of wired and wireless networking
- Optional Wireless LAN Module available
- Gigabit Ethernet enables fast transfer of large colour files across the network
- Google Cloud Print 2.0 ready, enabling printing on the move




Easy to use

- Easy to set-up and get started
- Store templates and documents on the device for all users to print without authentication (Shared Print)
- When new features are available you can update the device via the OKI portal



Important security features

- Keep documents confidential with Private Print and optional Card Release, so users can view all print jobs before selecting which ones to print
- Internet Protocol Security (IPSec) compliance, ensuring securing that documents are safely sent and received



Cost and energy saving

- Print marketing materials in-house, thanks to outstanding print quality and media flexibility
- Deep Sleep mode saves energy, Auto-Off mode automatically powers down to less than 0.5W when not in use
- Toner Save to reduce cost, when printing draft or internal documents
- Duplex printing reduces paper usage
- Mono only printing when colour cartridges are empty
- Free consumables recycling programme
- LED technology means no moving parts for a longer life

| A3/A4 | ~ |
|-----------------------------------|---|
| Colour/Mono | ~ |
| Networked/Duplex | ~ |
| Prints A6 to 1321mm, up to 256gsm | ~ |
| 1 – 30 users | ~ |

C823, C833, C843 - Colour and Mono Printers

| | C823: A4: 23ppm colour/mono; A3: 13ppm colour/mono | | Standard DAM, 256MD, Maximum DAM, 7(0MD (C022)(0022) | |
|--|--|--|--|--|
| Print speed | C833/C843: A4: 35ppm colour/mono; A3: 20ppm colour/mono | Memory | Standard RAM: 256MB; Maximum RAM: 768MB (C823/C833); Standard RAM: 512MB; Maximum RAM: 768MB (C843) | |
| | C823: 14 seconds colour/mono | - | Optional SDHC Memory Card ⁴ : 16GB | |
| Time to first print | C833/C843: 9.5 seconds colour/mono | Operating temperature/humidity: 10°C to 32°C (17°C to 27° Environment recommended) / 20% to 80% RH (50% to 70% RH recommended) | | |
| Warm up time | Approx. 25 seconds from power on and approx. 20 seconds from power save | | Storage temperature/humidty: -10°C to 43°C, 10% to 90% RH | |
| | approx. 20 seconds from power save | Power supply | Single phase 220-240VAC, frequency 50/60Hz +/-2% | |
| INTERFACE AND SOFTWARE Connectivity | USB 2.0 Device, 10Base-T/100Base-TX/1000Base-T Ethernet, | Power consumption | Typical: 700W; Max: <1400W; Idle: 100W; Power Save: <12W; Deep Sleep: <1.0W; Auto-Off: <0.15W | |
| , | USB 2.0 Host x 1, Wireless IEEE802.11a/b/g/n (Optional) C823: PCL6 (XL3.0) and PCL5c, SIDM (IBM-PPR, EPSON-FX), XPS | Noise level | Operating: <52dB(A); Standby: 32dB(A) or less; Power save: Background level | |
| Printer languages | C833/C843: PCL6 (XL3.0) and PCL5c, PostScript3 emulation, | Dimensions (WxDxH) | 449 x 552 x 360mm | |
| | PDF v1.7, SIDM (IBM-PPR, EPSON-FX), XPS | Weight ⁵ | 37kg approx (n models); 40kg approx (dn models) | |
| internal web server for management. TCP/IPv4 BOOTP, HTTP, HTTPs, DI SMTP, POP3, SNMPv1& IEEE802.1X, LPR, Port9 Wireless IEEE802.11a/I Enterprise | All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IPv4&v6, NetBIOS over TCP, DHCP, DHCPv6, BOOTP, HTTP, HTTPS, DNS, DDNS, WINS, UPNP, Bonjour, SMTP, POP3, SMMPv1&v3, SNTP, IPP, IPPS, WSD Print, LLTD, UFCF0014V, UPD, Devided TOT, Careada Cleard Brite | Duty cycle | Maximum: 75,000 pages/month; Recommended: 1,500 to 5,000 pages/month | |
| | | Warranty | 3 years extended warranty upon registration within 30 days of purchase | |
| | IEEE802.1X, LPR, Port9100, Telnet, FTP, Google Cloud Print, Wireless IEEE802.11a/b/g/n, WEP, WPA, WPA2, Personal, Enterprise Windows Vista (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / | Product order numbers | C823n: 46550701 (2AC) / 46471514 (Euro) / 46550801 (UK) (C823dn: 46550703 (2AC) / 46550702 (Euro) / 46550802 (UK) (C833n: 46550704 (2AC) / 46396614 (Euro) / 46550803 (UK) (C833dn: 46550706 (2AC) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (2AC) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (2AC) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (2AC) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (2AC) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (2AC) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (2AC) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (2AC) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (Euro) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (Euro) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (Euro) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (Euro) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (Euro) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (Euro) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (Euro) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (Euro) / 46550705 (Euro) / 46550804 (UK) (C833dn: 46550706 (Euro) / 46550705 (Euro) / 46550804 (UK) (C8340) (Euro) / 46550705 (Euro) / 46550705 (Euro) / 46550804 (UK) (C8340) (Euro) / 46550705 (Euro) / 46550804 (UK) (C8340) (Euro) / 46550705 (Euro) / 46550705 (Euro) / 46550804 (UK) (C8340) (Euro) / 46550805 (Euro) / 46550705 (Euro | |
| OS Compatibility ¹ | Windows 7 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Windows 8 (32-bit & 64-bit) / Server 2012 (64-bit) / Windows 8.1 (32-bit & | | C843dn: 46550707 (2AC) / 46468704 (Euro) / 46550805 (UI | |
| | 64-bit) / Server 2012 R2 (64-bit) / Windows 10 (32-bit & 64-bit); Linux PPD; Mac OS X 10.8.5 to 10.11 | Accessories (Order Nume | | |
| Advanced networking & security | IPv6, 802.1x authentication, SNMP V3, SSL3/TLS HTTPS encryption, Secure Print ² , Secure Erase ² , Data Encryption ² , IP filtering, IPSec | Memory | | |
| | | SDHC Memory Card ⁴ | | |
| | | 2nd/3rd ⁷ /4th ⁷ paper tray Banner tray | | |
| Utility suite ¹ | Template Manager ³ , Color Correct, OKI LPR ³ , Color Swatch Utility ³ , smart PrintSuperVision ³ , Print Job Accounting Client, Web Driver Installer ³ , Network Card Setup ⁶ , Configuration Tool ³ , PS Gamma Adjuster ⁷ , PDF Direct Print ^{3/7} , Firmware Update Tool, | Cabinet | | |
| | | Pedestal with castors | | |
| | | Duplex | | |
| | Profile Assistant ⁶ | Wireless LAN Module | | |
| Typefaces | | IC Reader Holder | | |
| C823: Scalable: 87 PCL fonts, PCL Bitmap fonts: LinePrinter, OCR-A/B, USPS ZIP Barcode | | Consumables (Order Numbers) | | |
| Printer fonts | C833/C843: Scalable: 87 PCL fonts and 80 PostScript fonts, PCL Bitmap fonts: LinePrinter,OCR-A/B, USPS ZIP Barcode | Toner cartridges* (7,000 pages) | Cyan: 46471103; Magenta: 46471102; Yellow: 46471101; Black: 46471104 | |
| Barcode | 10 types of one dimension with 26 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET, 2 types of two dimensions: PDF417, QR code | Toner cartridges ⁷ * (10,000 pages) | Cyan: 46443103; Magenta: 46443102; Yellow: 46443101; Black: 46443104 | |
| | | Image drums** (30,000 pages) | Cyan: 46438003; Magenta: 46438002; Yellow: 46438001; Black: 46438004 | |
| PRINT QUALITY | | Transfer Belt | 44846204 | |
| Resolution | C823/C833: ProQ Multi-level technology, 1200 x 600dpi, 600 x 600dpi | (80,000 pages) Fuser Unit | | |
| | C843: 1200 x 1200dpi | (100,000 pages) | 1 | |
| Enhancements | Auto Color Balance, Photo Enhance via Driver (Windows PCL6 driver only) | *Toners: A4 pages yield compliant with ISO/ISC 19798. Printer shipped with toner for 2,500 A4 pages. **Drum: Average number of A4 pages printed. | | |
| Paper Handling | | - | | |
| Paper capacity | Tray 1: 300 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm | | | |
| Paper capacity optional trays | Tray 2: 535 sheets of 80gsm; Tray 3: 535 sheets of 80gsm; Tray 4: 535 sheets of 80gsm | | | |
| Maximum paper capacity | C823: 935 sheets of 80gsm C833/C843: 2,005 sheets of 80gsm | | | |
| Paper sizes | Tray 1: A3, A4, A5, A6, B4, B5; Tray 2/3/4: A3, A4, A5, B4, B5; Multi-purpose tray: A3, A4, A5, B4, B5, A6; 11 Envelopes (Com-10, DL, C5, C4), Custom size (up to 1321mm length including banner); Duplex: A3, A4, A5, B4, B5; Custom size: Width 148.5-297mm Length 182-431.80mm | | | |
| Paper weight | Tray 1: 64 to 220gsm; Tray 2/3/4: 64 to 176gsm; Multi-purpose tray: 64 to 256gsm; Duplex: 64 to 220gsm | | | |
| Duplex | Standard: C823dn, C833dn, C843dn; Optional: C823n, C833n | | | |
| | | | | |

Paper output 250 sheets face down, 100 sheets face up, 80gsm

¹Check local OKI website for latest driver releases and OS compatibility; ²SDHC Memory Card required; ³Windows only; ⁴Secure Digital High Capacity (SDHC) Memory Card supports up to 32GB. OKI is not responsible for any compatibility risk using non OKI genuine SDHC Memory Card; ⁵Including all consumables; ⁶MacOSX only; ⁷C833/C843 only

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.



3 Year Warrantv

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. For further information please visit www.okiwarranty.com/3year

Without registration, the standard pan-European 1 year warranty applies.





©2017 Oki Europe Ltd. Oki Europe Ltd. is part of the Oki Electric group of companies. Version 1.3 02/2017. Specification subject to change without notice. All trademarks acknowledged. Google Cloud Print is a trademark of Google Inc.

OKI EUROPE LTD.

Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44(0) 20 8219 2190 F+44(0) 20 8219 2199 WWW.OKI.COM/EU

