

ROTEX AIR PRO / XL / IND



Automatic rotation and complete clearance

- Standard 40x50 cm plate or 45x55 cm on XL version
- Optimal heat & pressure distribution
- Robust frame

User friendly :

- * Complete lateral clearance of the plate
- * Pneumatic closing & opening
- * Automatic rotation at the end of the cycle

- Suitable for laser transfer applications & pretreatment drying
- Ideal for medium production
- Manufactured in France
- 2-year guarantee on the machine
- 10-year guarantee on heating plate




180° reversible C-shaped lower part with Quick Release system


Accessories




Support table



Sponge plate



Set of plates



Nomex® cover



Laser pointer



Z.I. de Pastabrac 11260 ESPERAZA FRANCE

Tél. +33 (0)4 68 74 05 89 Fax +33 (0)4 68 74 24 08

e-mail : contact@sefa.fr - site : www.sefa.fr

Technical characteristics

Plates size	40 x 50 or 45 x 55 cm
Weight	115 Kg
Pressure	
- in 40 x 50 cm	732 gr/cm ²
- in 45 x 55 cm	592 gr/cm ²
Max temperature	220°C
Power supply	240 V
Electric power	3200 W
Amperage	14 A

Settings



New user friendly touch screen with recipes menus!

Recipes menu with adaptive regulation parameters depending on the job: flex, sublimation on textile, sublimation on rigid substrates, DTG...

Advanced electronics

- 9 recipes menus depending on the job
- Save up to 5 programs PER recipe
- Sleep mode
- Eco mode
- Double timer (main + pre-heat)
- Cycle counters
- Stop cycle function

From 0 to 600 sec (precision +/- 1%).

From 15 to 255°C (precision +/- 1%).

Heating time to reach 180°C : 10 min.

Accessories



Table TAB-98 PRO

Strong support table for SEFA heat presses.






Plate PLA-DRY M:

40x50cm sponge plate to dry pretreated clothes.



Set of 4 plates PLA-QR:

Useful for precise work.
Dimensions:
12 x 8 cm - 15 x 15 cm
12 x 45 cm - 25 x 30 cm



Nomex® cover HOU-50 :

Heat resistant NOMEX® cover to protect the lower plate and make the threading easier.



Laser pointer CROI-159:

1-laser system to position your transfers with a greater precision. Possibility to add a second laser on the ramp.

Dimensions

